

⇒ BIO-DGUM

Biodegradable dissolvant/anti-adherent/degreaser for cleaning asphalt, tar and bitumen residues

Description

Dissolvant/anti-adherent/degreaser BIO-DGUM is formulated to clean, degum, and protect equipment surfaces against adhesion of tar, asphalt, bitumen, adhesives, dust, and other dirt.

Characteristics and Benefits

- 2 in1 formula.
- Formulated to meet OECD 301B, OECD 201-202 and, 203 standards.
- Composed of a minimum of 80% renewable material.
- Biodegradable product.
- Limits adhesion and cleans sticky residues.
- Meets standards when used near bodies of water.
- Contains no solvent.
- Contains no VOC.
- Safe to use and store.

Types of Applications

BIO-D-GUM is a specially formulated product for asphalt paving, construction and mining industries. It allows to clean effectively sticky residues such as tar, asphalt, bitumen, and other products that stick to tools, excavators, machinery and various surfaces while respecting the environment.

Directions for Use

Apply the product in thin film with a sprayer. Follow basic hygiene rules when applying the product. To let soak for a few minutes until the stains soften. Rinse with water with a high pressure cleaner or hose. Makes cleaning excessively easy if applied before on tools (a thin protective film can remain).

Warning

Do not apply BIO-DGUM on rubber (ex. rotor drive belt) or on styrofoam.

Storage

Comply with applicable legislation regarding the storage of this product. Do not store with flammable materials and food products. In its original packaging, the product keeps 1 year.

Available Sizes

4L, 20 L, 55 L, 205 L, 1000 L

Product Code

#778

Characteristics	ASTM Test	Typical Values BIO-DGUM
Flash point:	D92	≤ 190°C
Fire point:		≤ 210°C
Pour point:	D97	-5°C
Density at 15°C:	D4052	0,8950 g/ml
Viscosity at 40°C:	D445	8 cSt
Viscosity at 100°C:	D445	2.76 cSt
V.O.C. emission:		None
Biodegradability:		100%
Color:		Light yellow